



LED TECHNOLOGY

4700 sqm
Illuminated area



Road maintenance



Security



Outdoor show



Special events




Military applications



Emergency

PLUG-IN Line



Operation: **POWER**
Inlet plug 32A - 230V
Outlet socket 32A - 230V

X-BOX
MANUAL

4x160W LED - 8M

T-ZERO PRO

X-BOX MANUAL




4x160W LED - 8M

T-ZERO PRO



FEATURES

- Telescopic galvanized sections
- 4x160W high efficiency LED heads
- On/off switch to light up the led heads
- Multi-directionally adjustable and tiltable by hands floodlights
- Guided main coiled cable to avoid damage during tower operation
- **Manual winch with automatic brake system**
- Max height 8 meters
- Minimum height when complete close 2,5mt
- Simple, rugged machine design and layout
- Galvanized metalwork after 80 µm industrial powder coated
- **Compact dimensions**
- Assembled on base
- 1150x1150mm base dimensions
- Sides forklift pockets
- Only one front opening door
- **Possibility to link to others towers**
- **Stackable**
- Complete with stabilizers
- 230V inlet plug
- 230V outlet socket



Dimensions & weight	Dimensions min (mm)		Dimensions max(mm)		Total weight (kg)
		1150x1150x2500 (LxWxH)		2350x2350x8000 (LxWxH)	
Floodlights	Type	Power (each)	Floodlights number	IP level	Illuminated area (sqm)
	Led	160W	4	65	4700
Mast	Lifting method	Max Height	Max Wind Speed	Safety brake	
	Manual	8 m	110 km/h	Mechanical and included in the winch	
Input&output	Inlet plug		Outlet socket		
	32A - 230V		32A - 230V		



TRIME® Sales Dept. +39 0382 406 252
www.trime.it - info@trime.it
Lighting Towers