designed and created for your needs

power and innovation



32 KVA combined power

6,5h run time



Designed to provide an exceptional level of performance for every work on site ensuring the right balance between power and ease of use

MGTP 15000/24 TH

T-ZEROPRO



more sustainable and environmentally friendly future



T-ZEROPRO







APPLICATIONS









FEATURES

- DSE 3110 controller
- Communication-centre device
- 48V/600A BMS to protect the batteries
- 4G/GPS Antenna + Modem
- Remote telemetry & management
- Auto recharge of the batteries
- Automatic peak shaving mode
- Sides forklift pockets & Central lifting hook
- Lockable control panel
- Main circuit breaker & Earth leakage relay
- Emergency Stop button
- Bunded tank
- 3-way valve for external tank
- Battery switch



HYBRID LINE

Code	RP117-15TS8
Dimensions	'
LxWxH(mm)	2180x1222x1585
Weight (Kg)	1470
Technical Data	
Continuous power (VA)	15000
Battery pack capacity (Wh)	23552
Capacity available DOD 80% (Wh)	18842
Voltage (V)	230/400
Frequency (Hz)	50
Inverter	·
Nominal power (VA)	5000
Q.ty	3
System voltage (V)	48
Max charging current (A)	70
Batteries	
Туре	LiFeP04
Q.ty	4
Nominal Voltage (V)	25,6
Nominal Capacity (Ah)	230
Cycle Life DOD 80%	>4000
Engine	
Brand	Yanmar
Model	4TNV88
Speed	1500
Cooling system	Water
Emission	Stage V
Fuel Tank (I)	320
Alternator	
Brand	Linz
Model	PRO 18M E/4
Rated output (kVA)	42
Frequency (Hz)	50
Power factor (cos φ)	0,8
Distribution panel	
Inlet Plug	1x 32A-400V
Outlet Sockets	1x 32A-400V
	1x 16A-400V
	1x 16A-230V
Performances	
Running time on batteries (h) 25% load	6,5
Running time on batteries (h) 50% load	3,0
	2,0
Running time on batteries (h) 75% load	2,0



Mat heating system for batteries to work in cold ambients

