HYBRID LINE

designed and created for your needs

power and innovation

12 KVA combined power

9,5h run time





Designed to provide an exceptional level of performance for every work on site ensuring the right balance between power and ease of use

MGTP 5000/12 TH

T-ZEROPRO



more sustainable and environmentally friendly future















APPLICATIONS









FEATURES

- DSE 3110 controller
- Communication-centre device

- Remote telemetry & management
- Auto recharge of the batteries
- Automatic peak shaving mode
- Sides forklift pockets & Central lifting hook
- Lockable control panel
- Main circuit breaker & Earth leakage relay
- Emergency Stop button
- Bunded tank
- 3-way valve for external tank
- Battery switch



Code	RP47-5MS11
Dimensions	
L x W x H (mm)	1700x1066x1450
Weight (Kg)	800
Technical Data	
Continuous power (VA)	5000
Battery pack capacity (Wh)	11776
Capacity available DOD 80% (Wh)	9421
Voltage (V)	230
Frequency (Hz)	50
Inverter	
Nominal power (VA)	5000
Q.ty	1
System voltage (V)	48
Max charging current (A)	70
Batteries	
Туре	LiFeP04
Q.ty	2
Nominal Voltage (V)	25,6
Nominal Capacity (Ah)	230
Cycle Life DOD 80%	>4000
Engine	7 1000
Brand	Kubota
Model	D1105
Speed	1500
Cooling system	Water
Emission	Stage V
Fuel Tank (I)	200
Alternator	
Brand	Zanardi
Model	PE28 2VS/4
Rated output (kVA)	8
Frequency (Hz)	50
Power factor (cos φ)	0,8
Distribution panel	
Inlet Plug	1x 32A-230V
Outlet Sockets	1x 32A-230V
Performances	1x 16A-230V
Running time on batteries (h) 25% load	9,5
Running time on batteries (h) 50% load	4,5
Running time on batteries (h) 75% load	3,0
Recharge time from engine (h)	5
Available optionals	<u> </u>



Mat heating system for batteries to work in cold ambients

