designed and created for your needs

power and innovation



RENTAL LINE

STAGE 5

185 L Fuel Tank capacity

Designed to provide an exceptional level of performance for every work on site ensuring the right balance between power and ease of use

MGTP 100 SS-FR



more sustainable and environmentally friendly future





GENSET MODEL









diesel engine driven generating set 1500 r.p.m.

APPLICATIONS









FEATURES

- Built in fuel tank
- Bunded tank
- 12V Battery
- Battery switch
- Forklift pocket
- Central lifting eye
- Exhaust gas silencer
- Soundproof canopy
- 3 ways valve for external fuel tank connection



Code	RP361-100TS5
Dimensions	
LxWxH(mm)	2550 x 1130 x 1640
Weight (Kg)	1680
Technical Data	
PRP Prime Power (kVA)	100
LTP Limited Time Power (kVA)	110
Prime Power (cos $\phi = 0.8$)(kW)	80
Limited Time P. (cos $\phi = 0.8$)(kW)	88
Three-phase Voltage (V)	400
Single-phase Voltage (V)	230
Power factor (cos φ)	0,8
Frequency (Hz)	50
RPM	1500
Generator	
LINZ / MECC ALTE / STAMFORD	
Insulation Class	Н
Mechanical protection	IP23
Engine	
Туре	FTP IVECO F36 ETVP03.A94
EU Emission Stage	Stage V
Cylinders (n.)	4
Displacement (cm ³)	3400
Speed regulation	Electrical
Cooling	Water
Fuel	Diesel
Oil sump capacity (I)	8
Fuel Consumption	
Fuel Tank capacity (I)	185
Fuel consumption 75% load PRP (I/h)	17,8
<u> </u>	-
Running time (h)	10,5
Noise level	
Noise level (Lwa)	90
Acoustic pressure level 7m (dBA)	65
Distribution panel:	
1x 63A 400V EEC with MCB	
1x 32A 400V EEC with MCB	
1x 32A 230V EEC with MCB + ELCB	
1x 16A 230V EEC with MCB + ELCB	
Hardwire	
ELR	
On board control panel equipped with:	
DSE 7310	
ON/OFF switch	
Safety cover for DSE 7310 and ON/OFF sv	vitch
Main circuit breaker	
Earth leakage relay	
Remote start/stop connector	
Emergency stop	

