

Model: IVRN5-225 - RENTAL RANGE

400/230 V - THREE-PHASE | 1.500 R.P.M. | 50 Hz

RENTAL Genset with manual control panel.



Image for guidance purposes.



## PRP

**CONTINUOUS POWER:** 200 kVA

PRP "Prime Power" norma ISO 8528-1

## LTP

**STAND-BY POWER:** 219 kVA

LTP "Limited Time Power" norma ISO 8528-1

## ENGINE

| MAKE  | MODEL       |
|-------|-------------|
| VOLVO | TAD881GE-SV |

## ALTERNATOR

| MAKE        | MODEL    |
|-------------|----------|
| LEROY-SOMER | TAL044-M |

| VOLTAGE | HZ   | PHASE | COS Ø | PRP kVA/kW  | LTP kVA/kW  | AMP. (LTP) |
|---------|------|-------|-------|-------------|-------------|------------|
| 400/230 | 50Hz | 3     | 0,8   | 200,0/160,0 | 218,8/175,0 | 315,81     |

Rev.: 22/01/2024



Thiet GmbH  
Gutenbergstraße 3 - 26632 Ihlow / Riepe  
Telefon +49 4928 9192 - 26  
Web [www.thiet.de](http://www.thiet.de)

Model: IVRN5-225 - RENTAL RANGE

400/230 V - THREE-PHASE | 1.500 R.P.M. | 50 Hz

## ENGINE CHARACTERISTICS



| MAKE | MODEL |
|------|-------|
|------|-------|

VOLVO

TAD881GE-SV

### General Data

|                          |               |
|--------------------------|---------------|
| Power PRP (kWm)          | 172           |
| Power LTP (kWm)          | 189           |
| No. cylinders            | 6             |
| Cylinder capacity (L)    | 7.7           |
| Diameter per stroke (mm) | 110 x 135     |
| Compression ratio        | 17.2          |
| Cooling system           | LIQUID        |
| Injection                | COMMON RAIL   |
| Suction                  | TURBO-INTERC. |
| Series regulator         | ELECTRONIC    |
| Fly wheel coupling       | 2-11.5        |

### Lubrication system

|                               |      |
|-------------------------------|------|
| Oil capacity (L)              | 27   |
| Oil consumption (%)           | 0.04 |
| Min. alarm oil pressure (bar) | 2.07 |

### Ventilation system

|                                   |     |
|-----------------------------------|-----|
| Air cooling flow (m³/h)           |     |
| Combustion air flow (m³/h)        | 732 |
| Max. back pressure for fan (mbar) |     |

### Exhaust system

|                              |      |
|------------------------------|------|
| Exhaust gas flow (m³/h)      | 1758 |
| Exhaust back pressure (mbar) | 50   |
| Temp. exhaust gases (°C)     | 464  |

### Electrical system

|                      |         |
|----------------------|---------|
| VDC (V)              | 24      |
| Battery (Ah)         | 2 x 120 |
| Engine start-up (kW) | 5       |

Rev.: 22/01/2024



Thiet GmbH  
Gutenbergstraße 3 - 26632 Ihlow / Riepe  
Telefon +49 4928 9192 - 26  
Web [www.thiet.de](http://www.thiet.de)

Model: IVRN5-225 - RENTAL RANGE

400/230 V - THREE-PHASE | 1.500 R.P.M. | 50 Hz

## ALTERNATOR CHARACTERISTICS

| MAKE        | MODEL    |
|-------------|----------|
| LEROY-SOMER | TAL044-M |

### General Data

|                       |            |
|-----------------------|------------|
| Power PRP (kVA)       | 200        |
| Power LTP (kVA)       | 220        |
| Efficiency Alt. 100 % | 93         |
| Efficiency Alt. 110 % | 92.6       |
| No. Poles             | 4          |
| Voltage regulator     | AREP+ R180 |
| No. wires             | 6          |
| Insulation            | H          |
| Xd (%)                | 381        |
| X'd (%)               | 18.8       |
| X                     | 11.3       |
| Degree of protection  | IP23       |

## GENERATOR SET CONSUMPTION

| % POWER USED | LITRES/HOUR |
|--------------|-------------|
| 50%          | 21.8        |
| 75%          | 32          |
| 100%         | 42.7        |

## DIMENSIONS, CAPACITIES, APPROXIMATE WEIGHT

| Dimensions (mm) |       |        |
|-----------------|-------|--------|
| LENGTH          | WIDTH | HEIGHT |
| 4240            | 1200  | 2300   |

| FUEL TANK (LITRES) | WEIGHT (KG) |
|--------------------|-------------|
| 1100               | 3660        |

Model: IVRN5-225 - RENTAL RANGE

400/230 V - THREE-PHASE | 1.500 R.P.M. | 50 Hz

## INMESOL GENERATOR SET

### GENERAL DESCRIPTION

The “INMESOL” generator set is an electrical energy generating machine which is used in places where there is **no mains supply** or when there is a MAINS failure.

The mobile elements, distribution belt, fan, etc., and those parts which reach high temperatures during operation, exhaust manifold, etc, include their corresponding protections, in compliance with the requirements of the Machinery Directive **2006/42**.



**INMESOL S.L company with ISO 9001 quality certification system for the:**

Design, manufacture, marketing and technical assistance of power GENSETS, lighting towers, welding GENSETS, tractor with PTO GENSET and hybrid generation systems.

### Europe regulations:

Inmesol power GENSET sets comply with European legislation and were given the CE marking which includes the following directives:

- 2006/42/EC on machinery safety.
- 2005/88/EC on NOISE EMISSIONS by equipment for outdoor use (amends the 2000/14/EC).
- 2014/30/UE on Electromagnetic Compatibility.
- 2014/35/UE on electrical safety, electrical equipment designed to be used within certain voltage limits

### International regulations:

Upon request, INMESOL can supply equipment that complies with the International Legislation and Regulations:

- “Technical Regulation on Safety of Machinery & Equipment” No. 753, repealing GOST R standards for exports to Russia.
- Resolution n° 90708 dated August 30th 2013 “Reglamento Técnico de Instalaciones Eléctricas RETIE” issued by the Ministry of Mining and Energy, Section 20.21 Engines and power generators, for exports to Colombia.

### Information:

The power ratings are for reference to environmental conditions: barometric pressure 100 kPa, 25°C and 30% relative humidity. These are defined by ISO 8528 and ISO 3046.

PrimePower (PRP) “Main Service” is applicable for power GENSETS that function as main electric power source. It may be overloaded by 10% in limited time points, maximum once every 12 hours.

StandbyPower (LTP) “Emergency Service” applies to power GENSETS that run during Electrical Grid failure. This power may NOT BE OVERLOADED.

Nevertheless, to obtain long engine life, it is recommended that the active power average load (kW) connected to the power GENSET set in any period of 24 hours of operation does not exceed the following values:

- In Main Service 70% of the PRP power.
- In Emergency Service during Electrical Grid failure 80% of the LTP power.

Model: IVRN5-225 - RENTAL RANGE

400/230 V - THREE-PHASE | 1.500 R.P.M. | 50 Hz

**RR** RENTAL  
RANGE

## Scope of supply



Engine/alternator assembly, coupled and installed on a heavy electric welded steel profile base frame through antivibration pad, then treated with rust removing products for zinc layer application and Polyester (QUALICOAT) painting, "special treatment for external and corrosive environment."

Soundproof canopy treated with rust removing products for zinc layer application and Polyester (QUALICOAT) painting, "special treatment for external and corrosive environment." Then lined with rock wool material of high density.

Liquid cooled engine with integrated mechanical radiator and blower fan.

Residential exhaust silencer with -35 dB(A) attenuation, plus industrial silencer in line, with gases release protected by a cap.

Lifting hook crane.

Fork lift pockets for easy lifting from the bottom.

Hook for towing.

Radiator water filling cover register.

Easy access to radiator cleaning, and replacement.

Integrated metallic fuel tank of 24 hours autonomy with liquid leakage protection.

Large fuel tank register for cleaning.

Fuel draining plug.

Protection of heat, mobile, and live components.

Manual oil sump pump.

Baseframe prepared to be mounted on a trailer.

External emergency stop push button.

Heavy-duty engine starting battery complete with wires connection, terminal protection and on-off switch.

Alternator battery charger with earth plug.

Self excited and auto regulated alternator.

Manual control panel with a microprocessor for control, protection and generating set reading parameters as voltage, amperage, working hours, etc.

Circuit breaker 4P and regulable earth leakage.

Prepared for earth stud installation (earth stud not included).

Vertical warm air release, except in engines with exhaust gas after-treatment systems.

On/off battery switch.

Documents Bag.

Door retainer.

Cables lock for fixing the power cables.

Special anti vibration mounts fitted between the alternator/engine block and the frame, to decrease the amount of vibrations that are transmitted to the frame and to absorb all mechanical shocks from transportation.

Step/s for making easier the access to the lifting hook.

## OPTIONS

Coolant preheating resistor.

Battery charger.

Automatic/manual fuel transfer pump.

Alternator with enhanced protection against harsh environments.

Different colour.

External linkbox for armoured cables.

Kit of 3-way valves for external fuel tank connection (optional single lever).

Fast fuel plug connection between external and internal fuel tanks.

AMF/ATS panel to turn a manual gen set to automatic version.

Voltage and frequency change selector (50 Hz - 60 Hz), according to the model.

Sockets kits integrated in the canopy.

Soundproof canopy auxiliary internal lighting.

Upgrades to switchboards from other brands.

Internal fuel filler cap with security lockable key.

Synchronising control panels, for paralleling in island mode or with the utility.

Model: IVRN5-225 - RENTAL RANGE

400/230 V - THREE-PHASE | 1.500 R.P.M. | 50 Hz

## DEIF AGC-150 STANDALONE MANUAL CONTROL PANEL

MANUAL CONTROL, PROTECTION AND DISTRIBUTION panel, built in a metal cabinet fitted on the generating set, with control unit DEIF AGC-150 STANDALONE.



Image for guidance purposes.

It has the following:

### 1. EMERGENCY STOP PUSHBUTTON

### 2. PROTECTIONS

Main circuit breaker.

Earth leakage protection.

Protection fuses for control unit.

Rev.: 22/01/2024

Model: IVRN5-225 - RENTAL RANGE

400/230 V - THREE-PHASE | 1.500 R.P.M. | 50 Hz

## DEIF AGC-150 STANDALONE MANUAL CONTROL PANEL

### 3. DEIF AGC-150 STANDALONE CONTROL UNIT

#### LCD SCREEN:

It has a digital LCD screen, which provides easy reading of the information regarding the ENGINE, ALTERNATOR and LOAD.

| ENGINE                     | ALTERNATOR AND LOAD                           |
|----------------------------|-----------------------------------------------|
| Coolant temperature. *     | Phase to phase and phase to neutral voltages. |
| Oil pressure. *            | Currents.                                     |
| Running speed (rpm).       | Frequency.                                    |
| Fuel level.                | Active power (kW).                            |
| Battery voltage.           | Reactive power (kVAr).                        |
| Charge alternator voltage. | Apparent power (kVA).                         |
| Running hours.             | Power factor (cos $\phi$ ).                   |
| Number of starts.          | Active energy meter (kW-h).                   |

\* In generating sets equipped with the corresponding sensor.

#### CONTROL OF THE SET:

STARTS AND STOPS the set MANUALLY.

Possibility of doing it AUTOMATICALLY via REMOTE START SIGNAL.

#### PROTECTION OF THE ENGINE AND ALTERNATOR, WITH THE ALARMS ACTIVATED:

| ENGINE                       | ALTERNATOR                      |
|------------------------------|---------------------------------|
| Low oil pressure.            | Low and high voltage.           |
| High coolant temperature.    | Low and high frequency.         |
| Low and high battery voltage | Overload due to current (A).    |
| Charge alternator failure.   | Overload due to power (kW-kVA). |
| Low fuel level.              | Short-circuit.                  |
| Low load.                    | Negative phase sequence.        |

#### OTHER CHARACTERISTICS:

|                                                      |                                                          |
|------------------------------------------------------|----------------------------------------------------------|
| Fully configurable via PC software.                  | Real-time clock for an accurate record of events.        |
| Extensive number of configurable inputs and outputs. | Programmer clock for the optimal maintenance of the set. |
| Configurable alarms and timers.                      | Data logging function.                                   |
| USB connectivity.                                    | PLC functionality.                                       |
| RS485 port for MODBUS RTU.                           | Compatible with EU Stage V and EPA Tier 4 Final engines. |
| Ethernet port for MODBUS TCP/IP.                     |                                                          |

Model: IVRN5-225 - RENTAL RANGE

400/230 V - THREE-PHASE | 1.500 R.P.M. | 50 Hz

**DEIF AGC-150 STANDALONE MANUAL CONTROL PANEL****4. PROTECTIONS**

| MAGNETO. PROTECTION (A) | EARTH LEAK PROTECTION  | DISTRIBUTION    |
|-------------------------|------------------------|-----------------|
| 400A, 4P                | Electronic, adjustable | Power terminals |

Rev.: 22/01/2024



Thiet GmbH  
Gutenbergstraße 3 - 26632 Ihlow / Riepe  
Telefon +49 4928 9192 - 26  
Web [www.thiet.de](http://www.thiet.de)