RENTAL LINE STAGE 5

power and innovation



138 L Fuel Tank capacity

्या

POWER Division

00

designed and created for your needs

Designed to provide an exceptional level of performance for every work on site ensuring the right balance between power and ease of use

TPGR 20TY5







TPGR 20TY5

GENSET MODEL



diesel engine driven generating set 1500 r.p.m.

APPLICATIONS









FEATURES

- 😤 Built in fuel tank
- 🥺 Bunded tank
- 👳 12V Battery
- 🥺 Battery switch
- 👳 Forklift pocket
- 🥺 Central lifting eye
- 🥺 Exhaust gas silencer
- 👳 Soundproof canopy
- 👳 3 ways valve for external fuel tank connection



Code	RP351-20TS0
Dimensions	
_ x W x H (mm)	2200 x 1160 x 1620
Veight (Kg)	700
Fechnical Data	
PRP Prime Power (kVA)	20
TP Limited Time Power (kVA)	21
Prime Power (cos φ = 0,8)(kW)	16
imited Time P. ($\cos \phi = 0.8$)(kW)	16,8
Fhree-phase Voltage(V)	400
Single-phase Voltage (V)	230
Power factor (cos φ)	0,8
Frequency (Hz)	50
RPM	1500
Generator	
INZ / MECC ALTE / STAMFORD	
nsulation Class	Н
1echanical protection	IP23
Engine	1
Гуре	YANMAR 4TNV88
EU Emission Stage	Stage V
Cylinders (n.)	4
Displacement (cm ³)	2216
Speed regulation	Mechanical
Cooling	Water
Fuel	Diesel
Dil sump capacity (I)	10,6
Fuel Consumption	
Fuel Tank capacity (I)	136
Fuel consumption 75% load PRP(I/h)	4,0
Running time (h)	32
Noise level	V2
	90
Noise level (Lwa)	90
Acoustic pressure level 7m (dBA)	65
Distribution panel:	
x 32A 400V EEC with MCB	
x 32A 230V EEC with MCB + ELCB	
x 16A 230V EEC with MCB + ELCB	
lardwire	
ELR	
On board control panel equipped with:	
DSE 7310	
DN/OFF switch	
Safety cover for DSE 7310 and ON/OFF s	WITCh
1ain circuit breaker	
Earth leakage relay	
Remote start/stop connector	

Thiet GmbH Gutenbergstraße 3 26636 Ihlow/Riepe +49 4928 9192-0

Herstellerangaben ohne Gewähr. Bilder können vom tatsächlichen Produkt abweichen.