designed and create for your needs

Designed to provide an exceptional level of performance for every work on site ensuring the right balance between power and ease of use

MGTP 30 SS-YR

RENTAL LINE STAGE 5

power and innovation



185 L Fuel Tank capacity



more sustainable and environmentally friendly future





GENSET MODEL











diesel engine driven generating set 1500 r.p.m.

APPLICATIONS









FEATURES

- Built in fuel tank
- Bunded tank
- 12V Battery
- Battery switch
- Forklift pocket
- Central lifting eye
- Exhaust gas silencer
- Soundproof canopy
- 3 ways valve for external fuel tank connection



Code	RP352-32TS0
Dimensions	
LxWxH(mm)	2300 x 1130 x 1580
Weight (Kg)	1050
Technical Data	
PRP Prime Power (kVA)	32
LTP Limited Time Power (kVA)	35
Prime Power (cos ϕ = 0,8)(kW)	25,6
Limited Time P. (cos $\phi = 0.8$)(kW)	28
Three-phase Voltage (V)	400
Single-phase Voltage (V)	230
Power factor (cos φ)	0,8
Frequency (Hz)	50
RPM	1500
Generator	
LINZ / MECC ALTE / STAMFORD	
Insulation Class	Н
Mechanical protection	IP23
Engine	
Туре	YANMAR 4TNV98C-IYE
EU Emission Stage	Stage V
Cylinders (n.)	3
Displacement (cm³)	1861
Speed regulation	Electrical
Cooling	Water
Fuel	Diesel
Fuel Consumption	
Fuel Tank capacity (I)	185
Fuel consumption 75% load PRP (I/h)	6,9
Running time (h)	27
Noise level	
Noise level (Lwa)	90
Acoustic pressure level 7m (dBA)	65
Distribution panel:	
1x 32A 400V EEC with MCB	
1x 32A 230V EEC with MCB + ELCB	
1x 16A 230V EEC with MCB + ELCB	
Hardwire	
ELR	
On board control panel equipped with:	
DSE 7310	
0N/0FF switch	
Safety cover for DSE 7310 and ON/OFF sw	ritch
Main circuit breaker	
Earth leakage relay	
Remote start/stop connector	
Emergency stop	
Options: Rental Kit	
5 x 16A 230V + 1 x 32A 400 V + 1 x 63A 400\	/ with ELCB protection
Options	

