# designed and created for your needs

Designed to provide an exceptional level of performance for every work on site ensuring the right balance between power and ease of use

<u>MGTP</u> 45 SS-KR RENTAL LINE STAGE 5

# **power** and innovation



232 L Fuel Tank capacity



more sustainable and environmentally friendly future





GENSET MODEL



### KOHLER.







diesel engine driven generating set 1500 r.p.m.

# **APPLICATIONS**









# **FEATURES**

- Built in fuel tank
- Bunded tank
- 12V Battery
- Battery switch
- Forklift pocket
- Central lifting eye
- Exhaust gas silencer
- Soundproof canopy
- 3 ways valve for external fuel tank connection



Dimensions         L x W x H (mm)         2240 x 1196 x 1737           Weight (Kg)         1500           Technical Data         PRP Prime Power (kVA)         42           LTP Limited Time Power (kVA)         46           Prime Power (cos φ = 0,8)(kW)         33,6           Limited Time P. (cos φ = 0,8)(kW)         36,8           Three-phase Voltage (V)         230           Power factor (cos φ)         0,8           Frequency (Hz)         50           RPM         1500           Generator         LINZ / MECC ALTE / STAMFORD           Insulation Class         H           Mechanical protection         IP23           Engine         KOHLER KDI 2504TCR CA           Type         KOHLER KDI 2504TCR CA           EU Emission Stage         Stage V           Cylinders (n.)         4           Displacement (cm³)         2482           Speed regulation         Electrical           Cooling         Water           Fuel Consumption         232           Fuel Consumption 75% load PRP (I/h)         8,6           Running time (h)         22           Noise level         Noise level (Lwa)         90           Noise level (Lwa)         90
Technical Data
Technical Data
Technical Data
PRP Prime Power (kVA)         42           LTP Limited Time Power (kVA)         46           Prime Power (cos φ = 0,8)(kW)         33,6           Limited Time P. (cos φ = 0,8)(kW)         36,8           Three-phase Voltage (V)         230           Power factor (cos φ)         0,8           Frequency (Hz)         50           RPM         1500           Generator         LINZ / MECC ALTE / STAMFORD           Insulation Class         H           Mechanical protection         IP23           Engine         Type           Type         KOHLER KDI 2504TCR CA           EU Emission Stage         Stage V           Cylinders (n.)         4           Displacement (cm³)         2482           Speed regulation         Electrical           Cooling         Water           Fuel         Diesel           Fuel Consumption         232           Fuel consumption 75% load PRP (I/h)         8,6           Running time (h)         22           Noise level         Noise level           Noise level (Lwa)         90           Acoustic pressure level 7m (dBA)         65           Distribution panel:         1x 32A 400V EEC with MCB
LTP Limited Time Power (kVA)       46         Prime Power (cos φ = 0,8)(kW)       33,6         Limited Time P. (cos φ = 0,8)(kW)       36,8         Three-phase Voltage (V)       230         Power factor (cos φ)       0,8         Frequency (Hz)       50         RPM       1500         Generator       LINZ / MECC ALTE / STAMFORD         Insulation Class       H         Mechanical protection       IP23         Engine       Type         Type       KOHLER KDI 2504TCR CA         EU Emission Stage       Stage V         Cylinders (n.)       4         Displacement (cm³)       2482         Speed regulation       Electrical         Cooling       Water         Fuel       Diesel         Fuel Consumption       232         Fuel consumption 75% load PRP(I/h)       8,6         Running time (h)       22         Noise level       90         Acoustic pressure level 7m (dBA)       65         Distribution panel:       1x 32A 400V EEC with MCB         1x 32A 400V EEC with MCB + ELCB       1x 32A 230V EEC with MCB + ELCB
Prime Power [cos φ = 0,8](kW)         33,6           Limited Time P. (cos φ = 0,8)(kW)         36,8           Three-phase Voltage (V)         400           Single-phase Voltage (V)         230           Power factor (cos φ)         0,8           Frequency (Hz)         50           RPM         1500           Generator         LINZ / MECC ALTE / STAMFORD           Insulation Class         H           Mechanical protection         IP23           Engine         Stage V           Type         KOHLER KDI 2504TCR CA           EU Emission Stage         Stage V           Cylinders (n.)         4           Displacement (cm³)         2482           Speed regulation         Electrical           Cooling         Water           Fuel         Diesel           Fuel Consumption         232           Fuel consumption 75% load PRP (I/h)         8,6           Running time (h)         22           Noise level         Noise level (Lwa)         90           Acoustic pressure level 7m (dBA)         65           Distribution panel:         1x 63A 400V EEC with MCB           1x 32A 400V EEC with MCB + ELCB         1x 16A 230V EEC with MCB + ELCB
Limited Time P. (cos φ = 0,8)(kW)         36,8           Three-phase Voltage (V)         400           Single-phase Voltage (V)         230           Power factor (cos φ)         0,8           Frequency (Hz)         50           RPM         1500           Generator         LINZ / MECC ALTE / STAMFORD           Insulation Class         H           Mechanical protection         IP23           Engine         KOHLER KDI 2504TCR CA           Type         KOHLER KDI 2504TCR CA           EU Emission Stage         Stage V           Cylinders (n.)         4           Displacement (cm³)         2482           Speed regulation         Electrical           Cooling         Water           Fuel         Diesel           Fuel Consumption         Fuel Consumption           Fuel Tank capacity(I)         232           Fuel consumption 75% load PRP (I/h)         8,6           Running time (h)         22           Noise level         90           Acoustic pressure level 7m (dBA)         65           Distribution panel:         1x 63A 400V EEC with MCB           1x 32A 230V EEC with MCB + ELCB         1x 32A 230V EEC with MCB + ELCB
Three-phase Voltage (V)         400           Single-phase Voltage (V)         230           Power factor (cos φ)         0,8           Frequency (Hz)         50           RPM         1500           Generator         LINZ / MECC ALTE / STAMFORD           Insulation Class         H           Mechanical protection         IP23           Engine         KOHLER KDI 2504TCR CA           Type         KOHLER KDI 2504TCR CA           EU Emission Stage         Stage V           Cylinders (n.)         4           Displacement (cm³)         2482           Speed regulation         Electrical           Cooling         Water           Fuel         Diesel           Fuel Consumption         Fuel consumption           Fuel Tank capacity (I)         232           Fuel consumption 75% load PRP(I/h)         8,6           Running time (h)         22           Noise level         90           Acoustic pressure level 7m(dBA)         65           Distribution panel:         1x 63A 400V EEC with MCB           1x 32A 230V EEC with MCB         1x 32A 230V EEC with MCB + ELCB           1x 16A 230V EEC with MCB + ELCB
Single-phase Voltage(V)         230           Power factor (cos φ)         0,8           Frequency (Hz)         50           RPM         1500           Generator         LINZ / MECC ALTE / STAMFORD           Insulation Class         H           Mechanical protection         IP23           Engine         KOHLER KDI 2504TCR CA           EU Emission Stage         Stage V           Cylinders (n.)         4           Displacement (cm³)         2482           Speed regulation         Electrical           Cooling         Water           Fuel         Diesel           Fuel Consumption         232           Fuel consumption 75% load PRP (I/h)         8,6           Running time (h)         22           Noise level         Noise level (Lwa)         90           Acoustic pressure level 7m (dBA)         65           Distribution panel:         1x 63A 400V EEC with MCB           1x 32A 230V EEC with MCB + ELCB         1x 16A 230V EEC with MCB + ELCB
Power factor (cos φ) Frequency (Hz) Frequency (Insulation Class Frequency (Insulation Cla
Frequency (Hz)   1500
RPM
Generator  LINZ / MECC ALTE / STAMFORD  Insulation Class H  Mechanical protection IP23  Engine  Type KOHLER KDI 2504TCR CA  EU Emission Stage Stage V  Cylinders (n.) 4  Displacement (cm³) 2482  Speed regulation Electrical  Cooling Water  Fuel Diesel  Fuel Consumption  Fuel Tank capacity (I) 232  Fuel consumption 75% load PRP (I/h) 8,6  Running time (h) 22  Noise level  Noise level (Lwa) 90  Acoustic pressure level 7m (dBA) 65  Distribution panel:  1x 63A 400V EEC with MCB  1x 32A 230V EEC with MCB  1x 32A 230V EEC with MCB + ELCB  1x 16A 230V EEC with MCB + ELCB
LINZ / MECC ALTE / STAMFORD  Insulation Class  Mechanical protection  Engine  Type  KOHLER KDI 2504TCR CA EU Emission Stage  Cylinders (n.)  Displacement (cm³)  Speed regulation  Cooling  Fuel  Diesel  Fuel Consumption  Fuel Tank capacity (I)  Running time (h)  Noise level  Noise level (Lwa)  Acoustic pressure level 7m (dBA)  Distribution panel:  1x 32A 400V EEC with MCB  1x 32A 230V EEC with MCB  1x 16A 230V EEC with MCB + ELCB
Insulation Class  Mechanical protection  IP23  Engine  Type  EU Emission Stage  Cylinders (n.)  Displacement (cm³)  Speed regulation  Cooling  Fuel  Fuel  Diesel  Fuel Consumption  Fuel Tank capacity (I)  Running time (h)  Noise level  Noise level  Noise level (Lwa)  Acoustic pressure level 7m (dBA)  Distribution panel:  1x 63A 400V EEC with MCB  1x 32A 230V EEC with MCB + ELCB  1x 16A 230V EEC with MCB + ELCB  IX 16A 230V EEC with MCB + ELCB
Engine Type KOHLER KDI 2504TCR CA EU Emission Stage Stage V Cylinders (n.) 4 Displacement (cm³) 2482 Speed regulation Electrical Cooling Water Fuel Diesel Fuel Consumption Fuel Tank capacity (I) 232 Fuel consumption 75% load PRP (I/h) 8,6 Running time (h) 22 Noise level Noise level (Lwa) 90 Acoustic pressure level 7m (dBA) 65 Distribution panel:  1x 63A 400V EEC with MCB 1x 32A 230V EEC with MCB + ELCB 1x 16A 230V EEC with MCB + ELCB
Engine  Type KOHLER KDI 2504TCR CA EU Emission Stage Stage V  Cylinders (n.) 4  Displacement (cm³) 2482  Speed regulation Electrical  Cooling Water  Fuel Diesel  Fuel Consumption  Fuel Tank capacity (I) 232  Fuel consumption 75% load PRP (I/h) 8,6  Running time (h) 22  Noise level  Noise level (Lwa) 90  Acoustic pressure level 7m (dBA) 65  Distribution panel:  1x 63A 400V EEC with MCB  1x 32A 230V EEC with MCB + ELCB  1x 16A 230V EEC with MCB + ELCB
Type  EU Emission Stage  Cylinders (n.)  Displacement (cm³)  Speed regulation  Cooling  Fuel  Fuel  Diesel  Fuel Consumption  Fuel Tank capacity (I)  Running time (h)  Noise level  Noise level (Lwa)  Acoustic pressure level 7m (dBA)  Distribution panel:  1x 63A 400V EEC with MCB  1x 32A 230V EEC with MCB + ELCB  1x 16A 230V EEC with MCB + ELCB
EU Emission Stage  Cylinders (n.)  Displacement (cm³)  Speed regulation  Electrical  Cooling  Water  Fuel  Diesel  Fuel Consumption  Fuel Tank capacity (I)  Running time (h)  Noise level  Noise level (Lwa)  Acoustic pressure level 7m (dBA)  Distribution panel:  1x 63A 400V EEC with MCB  1x 32A 230V EEC with MCB + ELCB  1x 16A 230V EEC with MCB + ELCB
Cylinders (n.)         4           Displacement (cm³)         2482           Speed regulation         Electrical           Cooling         Water           Fuel         Diesel           Fuel Consumption           Fuel Tank capacity (I)         232           Fuel consumption 75% load PRP (I/h)         8,6           Running time (h)         22           Noise level           Noise level (Lwa)         90           Acoustic pressure level 7m (dBA)         65           Distribution panel:         1x 63A 400V EEC with MCB           1x 32A 400V EEC with MCB         1x 32A 230V EEC with MCB + ELCB           1x 16A 230V EEC with MCB + ELCB         1x 16A 230V EEC with MCB + ELCB
Displacement (cm³)   2482
Speed regulation  Cooling  Water  Fuel  Diesel  Fuel Consumption  Fuel Tank capacity (I)  Running time (h)  Noise level  Noise level (Lwa)  Acoustic pressure level 7m (dBA)  Distribution panel:  1x 63A 400V EEC with MCB  1x 32A 230V EEC with MCB + ELCB  1x 16A 230V EEC with MCB + ELCB
Cooling         Water           Fuel         Diesel           Fuel Consumption         232           Fuel Tank capacity (I)         232           Fuel consumption 75% load PRP (I/h)         8,6           Running time (h)         22           Noise level         90           Acoustic pressure level 7m (dBA)         65           Distribution panel:         1x 63A 400V EEC with MCB           1x 32A 400V EEC with MCB         1x 32A 230V EEC with MCB + ELCB           1x 16A 230V EEC with MCB + ELCB
Fuel Diesel  Fuel Consumption  Fuel Tank capacity (I) 232  Fuel consumption 75% load PRP (I/h) 8,6  Running time (h) 22  Noise level  Noise level (Lwa) 90  Acoustic pressure level 7m (dBA) 65  Distribution panel:  1x 63A 400V EEC with MCB  1x 32A 400V EEC with MCB  1x 32A 230V EEC with MCB + ELCB  1x 16A 230V EEC with MCB + ELCB
Fuel Consumption  Fuel Tank capacity (I) 232  Fuel consumption 75% load PRP (I/h) 8,6  Running time (h) 22  Noise level  Noise level (Lwa) 90  Acoustic pressure level 7m (dBA) 65  Distribution panel:  1x 63A 400V EEC with MCB  1x 32A 400V EEC with MCB  1x 32A 230V EEC with MCB + ELCB  1x 16A 230V EEC with MCB + ELCB
Fuel Tank capacity (I)  Fuel consumption 75% load PRP (I/h)  8,6  Running time (h)  22  Noise level  Noise level (Lwa)  Acoustic pressure level 7m (dBA)  Distribution panel:  1x 63A 400V EEC with MCB  1x 32A 400V EEC with MCB  1x 32A 230V EEC with MCB + ELCB  1x 16A 230V EEC with MCB + ELCB
Fuel consumption 75% load PRP(I/h)  Running time (h)  22  Noise level  Noise level (Lwa)  Acoustic pressure level 7m (dBA)  Distribution panel:  1x 63A 400V EEC with MCB  1x 32A 400V EEC with MCB  1x 32A 230V EEC with MCB + ELCB  1x 16A 230V EEC with MCB + ELCB
Running time (h)  Noise level  Noise level (Lwa)  Acoustic pressure level 7m (dBA)  Distribution panel:  1x 63A 400V EEC with MCB  1x 32A 400V EEC with MCB  1x 32A 230V EEC with MCB + ELCB  1x 16A 230V EEC with MCB + ELCB
Noise level (Lwa) 90  Acoustic pressure level 7m (dBA) 65  Distribution panel:  1x 63A 400V EEC with MCB  1x 32A 400V EEC with MCB  1x 32A 230V EEC with MCB + ELCB  1x 16A 230V EEC with MCB + ELCB
Noise level (Lwa)  Acoustic pressure level 7m (dBA)  Distribution panel:  1x 63A 400V EEC with MCB  1x 32A 400V EEC with MCB  1x 32A 230V EEC with MCB + ELCB  1x 16A 230V EEC with MCB + ELCB
Acoustic pressure level 7m (dBA)  Distribution panel:  1x 63A 400V EEC with MCB  1x 32A 400V EEC with MCB  1x 32A 230V EEC with MCB + ELCB  1x 16A 230V EEC with MCB + ELCB
Distribution panel:  1x 63A 400V EEC with MCB  1x 32A 400V EEC with MCB  1x 32A 230V EEC with MCB + ELCB  1x 16A 230V EEC with MCB + ELCB
1x 63A 400V EEC with MCB 1x 32A 400V EEC with MCB 1x 32A 230V EEC with MCB + ELCB 1x 16A 230V EEC with MCB + ELCB
1x 32A 400V EEC with MCB 1x 32A 230V EEC with MCB + ELCB 1x 16A 230V EEC with MCB + ELCB
1x 32A 230V EEC with MCB + ELCB 1x 16A 230V EEC with MCB + ELCB
1x 16A 230V EEC with MCB + ELCB
· · · · ·
Hardwire
ELR
On board control panel equipped with:
DSE 7310
ON/OFF switch
Safety cover for DSE 7310 and ON/OFF switch
Main circuit breaker
Earth leakage relay
Remote start/stop connector
Emergency stop
Options
Site tow trailer O