# designed and create for your needs

Designed to provide an exceptional level of performance for every work on site ensuring the right balance between power and ease of use

# MGTP 60 SS-KR

RENTAL LINE STAGE 5

# **power** and innovation



232 L Fuel Tank capacity



more sustainable and environmentally friendly future





GENSET MODEL











diesel engine driven generating set 1500 r.p.m.

### **APPLICATIONS**









## **FEATURES**

- Built in fuel tank
- Bunded tank
- 12V Battery
- Battery switch
- Forklift pocket
- Central lifting eye
- Exhaust gas silencer
- Soundproof canopy
- 3 ways valve for external fuel tank connection



Code	RP354-60TS0
Dimensions	
LxWxH(mm)	2240 x 1196 x 1737
Weight (Kg)	1600
Technical Data	
PRP Prime Power (kVA)	60
LTP Limited Time Power (kVA)	66
Prime Power ( $\cos \phi = 0.8$ )(kW)	48
Limited Time P. (cos $\phi = 0.8$ )(kW)	52,8
Three-phase Voltage (V)	400
Single-phase Voltage (V)	230
Power factor (cos $\phi$ )	0,8
	50
Frequency (Hz)	
RPM	1500
Generator	
LINZ / MECC ALTE / STAMFORD	
Insulation Class	H
Mechanical protection	IP23
Engine	T
Туре	KOHLER KDI 3404TCR CAC
EU Emission Stage	Stage V
Cylinders (n.)	4
Displacement (cm³)	3400
Speed regulation	Electrical
Cooling	Water
Fuel	Diesel
Fuel Consumption	
Fuel Tank capacity (I)	232
Fuel consumption 75% load PRP(I/h)	10,8
Running time (h)	17
Noise level	
Noise level (Lwa)	90
Acoustic pressure level 7m (dBA)	65
Distribution panel:	
1x 63A 400V EEC with MCB	
1x 32A 400V EEC with MCB	
1x 32A 230V EEC with MCB + ELCB	
1x 16A 230V EEC with MCB + ELCB	
Hardwire	
On board control manel agreement with	
On board control panel equipped with:	
DSE 7310	
ON/OFF switch	20.1
Safety cover for DSE 7310 and ON/OFF st	witch
Main circuit breaker	
Earth leakage relay	
Earth leakage relay Remote start/stop connector	
Remote start/stop connector	

