

VAR 1-110

Gasoline - Qmax 23 m³/h (100 USgpm) - Hmax 25,5 m (84 ft)



VAR - Self-priming centrifugal pumps

These self-priming centrifugal pumps are for applications where the main feature is the difficulty in priming. Even with suction heights of several meters the machine quickly evacuates the air from the suction pipe and starts pumping. Additionally, thanks to the semi-open impeller, the VAR range is also suitable for pumping liquids with solids in suspension.

Applications

Both Atlas Copco and Varisco have decades of experience in designing and producing pumps. We have put those years of expertise into providing a solutions portfolio that works across multiple applications. The VAR range is packed with features that not only meet, but exceed the needs of the market. We are focused on an efficient, extremely versatile pump that is suitable for many industries, including construction, general dewatering and emergency applications, such as flood clean up.

Benefits

Rapid self-priming

Without foot valve up to a height of 7.5 m (24.5 ft)

High resistance

To abrasive liquids and turbid sandy waters

Semi-open impeller

Solids handling up to 20 mm (0.8")

Easy maintenance

Removable front cover for direct access to the impeller

Wear plate

Cast iron or stainless steel (F10) wear plate, that is easily replaceable

VAR 1-110

Performance curves

Test according to UNI EN ISO 9906 standard - level 2


Test liquid: clean water, density $1,000 \text{ kg/m}^3$

Spherical solids handling: D.20 mm (0.8")

Priming time: 26 s from 1,5 m (4.9 ft)

Max absorbed power: 1,7 kW - 2.3 HP (3.600 rpm)

Recommended
operating range



VAR 1-110

Technical data

Pump

Model	VAR 1-110
Qmax	23 m³/h - 380 l/min (100 USgpm)
Hmax	25,5 m (84 ft)
Q max eff.	12 m³/h - 200 l/min (100 USgpm)
Eff. max	52 %
Suction port	threaded - 1 1/2" BSP
Delivery port	threaded - 1 1/2" BSP
Impeller type	Semi-Open, 3 vane
Solids handling	20 mm (0.8 ")
Material	G10
Casing	EN-GJL-200 cast iron
Impeller	EN-GJL-200 cast iron
Wear plates	EN-GJL-250 cast iron
Number of plates	1
Shaft	C45 steel
Mechanical seal	Silicon carbide / Silicon carbide
Elastomers	NBR

Engines

Make	Honda					
Model	GX120 (HD01)					
Type	Gasoline - aspirated					
Displacement	118 cm³ (7 in³)					
No. cylinders	1					
Cooling	Air					
Rpm type	Variable					
Standard speed	3.600 rpm					
EU emissions	N/Em					
Starting	Recoil					
Oil change interval	100 h					
Speed [rpm]	2000	2500	3000	3300	3600	
Consumption [l/h]	0,7	0,8	0,8	0,9	1	
Power [kW]	1,2	1,5	1,9	2	2,1	
Power [HP]	1.6	2	2.5	2.7	2.8	

VAR 1-110

Arrangements

Technical data

Material	S275JR EN 10025-2 carbon steel
Coatings	Bicomponent, average thickness of 80 µm
Color	Yellow and grey Atlas Copco (standard)
Features	Carrying frame with galvanised steel frame
Tank	2 l (0.5 USG)

VAR 1-110 B LIFT - R



Dimensions	350 x 485 x 515 mm 14 x 19 x 20 "
H suction port	0,21 m (0.7 ft)
Weight (HD01)	26 kg (60 lb)

VAR 1-110 B TROLLEY - R



Dimensions	610 x 765 x 980 mm 24 x 30 x 39 "
H suction port	0,4 m (1.3 ft)
Weight (HD01)	34 kg (70 lb)